

# 軸流ファン Axial Fan

## 40×40×20mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 26 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 9 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 30g (1.06oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type (8 holes)  
T : Rib Type (4holes)  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B . S . N	VDC	VDC	Amp	Watt	R . P . M	m <sup>3</sup> /min	CFM	mm Aq	INAq	dB-A
DG1204L	B	12	5~13.8	0.10	1.28	5000	0.16	5.60	3.34	0.131	22.6
DG1204M	B	12	5~13.8	0.11	1.32	6000	0.19	6.68	5.01	0.197	26.5
DG1204H	B	12	5~13.8	0.15	1.80	7000	0.22	7.64	6.16	0.243	29.5
DG1204G	B	12	5~13.8	0.18	3.16	8000	0.25	8.80	8.25	0.325	33.4
DG1204U	B	12	5~13.8	0.24	2.88	9000	0.28	10.00	8.59	0.377	36.6
DG1204S1	B	12	5~13.8	0.30	3.60	10000	0.32	11.10	12.09	0.476	40.5

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

